

Technical Memorandum

I-95 / US 322 INTERCHANGE TRAFFIC STUDY



April 2008



Delaware Valley Regional Planning Commission
190 North Independence Mall West, 8th Floor
Philadelphia, PA 19106-1520

Technical Memorandum

I-95 / US 322 INTERCHANGE TRAFFIC STUDY

April 2008



Delaware Valley Regional Planning Commission
190 North Independence Mall West, 8th Floor
Philadelphia, PA 19106-1520

Created in 1965, the Delaware Valley Regional Planning Commission (DVRPC) is an interstate, intercounty, and intercity agency which provides continuing, comprehensive, and coordinated planning to shape a vision for the future growth of the Delaware Valley region. The region includes Bucks, Chester, Delaware, and Montgomery counties as well as the City of Philadelphia, in Pennsylvania; and Burlington, Camden, Gloucester, and Mercer counties in New Jersey. DVRPC provides technical assistance and services, conducts high priority studies that respond to the request and demands of member state and local governments, fosters cooperation among various constituents to forge a consensus on diverse regional issues, determines and meets the needs of the private sector, and practices public outreach efforts to promote two-way communication and public awareness of regional issues and the commission.



Our logo is adapted from the official DVRPC seal, and is designed as a stylized image of the Delaware Valley. The outer ring symbolizes the region as a whole while the diagonal bar signifies the Delaware River. The two adjoining crescents represent the Commonwealth of Pennsylvania and the State of New Jersey.

DVRPC is funded by a variety of funding sources including federal grants from the U.S. Department of Transportation's Federal Highway Administration (FHWA) and Federal Transit Administration (FTA), the Pennsylvania and New Jersey departments of transportation, as well as by DVRPC's state and local member governments. The authors, however, are solely responsible for its findings and conclusions, which may not represent the official views or policies of the funding agencies.

DVRPC fully complies with Title VI of the Civil Rights Act of 1964 and related statutes and regulations in all programs and activities. DVRPC's website may be translated into Spanish, Russian, and Traditional Chinese online by visiting www.dvrpc.org. Publications and other public documents can be made available in alternative languages or formats, if requested. For more information, please call (215) 238-2871.

TABLE OF CONTENTS

I. INTRODUCTION	1
II. CHARACTERISTICS OF THE STUDY AREA	3
A. Current Average Daily Traffic Volumes	5
B. Current AM and PM Peak Hour Volumes	5
III. IMPROVEMENT ALTERNATIVES	11
A. No-Build Alternative	11
B. Build Alternative 1	11
C. Build Alternative 2	13
D. Build Alternative 3	13
IV. TRAVEL FORECASTING PROCEDURES	15
A. Socioeconomic Projections	15
1. Population Forecasting	15
2. Employment Forecasting	16
3. I-95 / US 322 Interchange Study Area Forecasts	16
B. DVRPC's Travel Simulation Process	18
1. Trip Generation	19
2. Evans Iterations	21
3. Trip Distribution	21
4. Modal Split	21
5. Highway Assignment	21
6. Transit Assignment	22
C. Highway Traffic Assignment Validation	22
V. PROJECTED TRAFFIC VOLUMES	23
A. 2014 Daily Traffic Forecasts	23
B. 2014 AM and PM Peak Hour Traffic Forecasts	33
C. 2034 Daily Traffic Forecasts	40
D. 2034 AM and PM Peak Hour Traffic Forecasts	52
VI. CONCLUSIONS	63

LIST OF TABLES

1. Study Area Population and Employment	17
2. Current and 2014 Average Daily Traffic Volumes	31
3. Current and 2034 Average Daily Traffic Volumes	43

LIST OF FIGURES

1. I-95 / US 322 Interchange Traffic Study Area	4
2. Current Average Daily Traffic Volumes	6
2A. Current Average Daily Traffic Volumes (Inset)	7
3. Current AM / PM Peak Hour Traffic Volumes	8
4. Proposed Improvements Under Build Alternatives 1, 2, and 3	12
5. DVRPC's Travel Modeling Process	20
6. Current and 2014 No-Build Alternative Average Daily Traffic Volumes	24
6A. Current and 2014 No-Build Alternative Average Daily Traffic Volumes (Inset) ..	25
7. 2014 No-Build and Build Alternatives 1, 2, and 3 Average Daily Traffic Volumes .	27
7A. 2014 No-Build and Build Alternative 1 Average Daily Traffic Volumes (Inset) ..	28
7B. 2014 No-Build and Build Alternative 2 Average Daily Traffic Volumes (Inset) ..	29
7C. 2014 No-Build and Build Alternative 3 Average Daily Traffic Volumes (Inset) ..	30
8. 2014 No-Build Alternative AM / PM Peak Hour Traffic Volumes	34
9. 2014 Build Alternative 1 AM / PM Peak Hour Traffic Volumes	36
10. 2014 Build Alternative 2 AM / PM Peak Hour Traffic Volumes	38
11. 2014 Build Alternative 3 AM / PM Peak Hour Traffic Volumes	41
12. Current and 2034 No-Build Alternative Average Daily Traffic Volumes	45
12A. Current and 2034 No-Build Alternative Average Daily Traffic Volumes (Inset) .	46
13. 2034 No-Build and Build Alternatives 1, 2, and 3 Average Daily Traffic Volumes	48
13A. 2034 No-Build and Build Alternative 1 Average Daily Traffic Volumes (Inset) ..	49
13B. 2034 No-Build and Build Alternative 2 Average Daily Traffic Volumes (Inset) ..	50
13C. 2034 No-Build and Build Alternative 3 Average Daily Traffic Volumes (Inset) ..	51
14. 2034 No-Build Alternative AM / PM Peak Hour Traffic Volumes	53
15. 2034 Build Alternative 1 AM / PM Peak Hour Traffic Volumes	56
16. 2034 Build Alternative 2 AM / PM Peak Hour Traffic Volumes	58
17. 2034 Build Alternative 3 AM / PM Peak Hour Traffic Volumes	60

I. INTRODUCTION

This memo, requested by the Pennsylvania Department of Transportation (PENNDOT), documents 2014 and 2034 traffic forecasts for the Interstate 95 / US 322 interchange and the surrounding area. In preparation for projecting future traffic volumes, traffic counts throughout the study area were collected by PENNDOT's consultants (DMJM Harris | AECOM) and the Delaware Valley Regional Planning Commission (DVRPC). Municipal and county planners were contacted to identify the significant proposed residential and commercial developments within the corridor. DVRPC's regional traffic simulation model was focused on the corridor and used to prepare 2014 and 2034 traffic volume estimates for study area roadways under a No-Build and three Build alternatives.

A focused travel simulation was conducted using DVRPC's regional travel forecasting models. The traffic zones in the study area were subdivided into smaller zones to better reflect the highway network and land use characteristics of the study area. The model's highway network within the study area was reviewed and modified as needed to reflect the detailed nature of the traffic improvements to be tested.

The forecasts from this traffic study will be used to evaluate alternative interchange configurations, design ramp merge and weave areas, assess the need for traffic signal and other intersection improvements at ramp junctions, and provide data for pavement design and maintenance of traffic during construction activities.

Chapter II of this memo documents the existing characteristics of the study area, including current daily and AM and PM peak hour traffic volumes. The alternatives analyzed in the study are described in Chapter III. Chapter IV explains the travel forecasting methodology, including a description of the travel simulation model used to develop the traffic projections. The study area's population and employment projections, which provide necessary inputs into the travel model, are also presented in this chapter. Chapter V presents an analysis of the projected 2014 and 2034 daily and peak hour traffic forecasts under each alternative. Finally, conclusions drawn from the traffic study are listed in Chapter VI.

[This page intentionally left blank]

II. CHARACTERISTICS OF THE STUDY AREA


The I-95 / US 322 interchange connects two heavily traveled corridors. Interstate 95 is the region's primary north-south corridor, providing connections between the cities of Wilmington, Delaware; Chester and Philadelphia in Pennsylvania; and Trenton, New Jersey. I-95 also connects the region to other major east coast cities, such as Boston, New York, and Washington, D.C. Traveling north, the highway enters Pennsylvania in Lower Chichester Township, Delaware County, and follows the Delaware River corridor. North of the City of Chester, I-95 connects to I-476, the Philadelphia International Airport, and the Philadelphia sports complex. I-95 carries three northbound and three southbound lanes in this area.

US 322 is an older highway that runs between Atlantic City, New Jersey and Cleveland, Ohio. It enters Pennsylvania from Gloucester County, New Jersey by crossing the Delaware River via the Commodore Barry Bridge. US 322 passes through Delaware and Chester counties and continues through Harrisburg and State College, Pennsylvania. US 322 is primarily a two-lane roadway, although between I-95 and PA 452 (Market Street), it is a four-lane facility.

The portion of I-95 between Exit 3 (West Chester) and Exit 4 (Commodore Barry Bridge) is designated as both I-95 and US 322. This concurrent section of I-95 and US 322, along with their interchange at I-95 Exit 3, is the focus of this traffic study. The traffic study is intended to support an interchange reconstruction project that will increase safety and improve the flow of traffic through the interchange. This project is intended to address a major weaving movement across three lanes of I-95 traffic. Currently, US 322 eastbound traffic merges with the left-most lane of I-95 northbound at Exit 3, and continues towards the Commodore Barry Bridge via a right-side off-ramp at Exit 4. Because of the close proximity of Exits 3 and 4, this weaving movement often causes conflicts with through traffic that result in chronic delays and numerous accidents.

Other issues to be addressed include sub-standard acceleration and deceleration lanes, clearance issues at the US 322 bridge over the Norfolk Southern rail line, other geometric problems associated with US 322 and Bethel Road, and the lack of a connection from US 322 eastbound to I-95 southbound. In addition, the project will improve access to large commercial developments surrounding the interchange and is intended to reduce congestion on other area facilities, such as PA 452.

The study area for traffic forecasting purposes is defined as the municipalities of Aston, Bethel, Chester, Lower Chichester and Upper Chichester townships; Chester City; and Brookhaven, Eddystone, Marcus Hook, Parkside, Trainer, and Upland boroughs in Delaware County. This area, along with its relationship to I-95 and US 322, is shown in Figure 1.



Delaware Valley Regional
 Planning Commission
 March 2008

A. Current Average Daily Traffic Volumes

Figure 2 displays the current average annual daily traffic (AADT) volumes for Interstate 95, US 322, their ramps, and other significant roadway facilities in the study area. Traffic volumes along I-95 in this area range from 110,200 to 145,900 vehicles per day (vpd). The highest volume occurs between Exits 3 and 4, where I-95 and US 322 come together. North of the Commodore Barry Bridge interchange (Exit 4), the I-95 traffic volume drops to 132,300 vpd, although this value does not include the 15,100 vehicles on the southbound collector-distributor roadway between Kerlin Street and Exit 4.

US 322 volumes west of I-95 range from 27,600 to 33,400 vpd. East of I-95, as it approaches the Commodore Barry Bridge, US 322 carries a slightly higher volume of 35,400 vpd. The next highest volume facility in the study area is PA 452, which carries between 16,800 and 23,600 vpd.

There are several high-volume ramps in the study area. These include the ramp from US 322 eastbound to I-95 northbound at Exit 3, which carries 13,800 vpd, and the corresponding I-95 southbound to US 322 westbound ramp, with a daily volume of 16,100 vehicles. The I-95 southbound off-ramp to Highland Avenue and the northbound on-ramp from Highland Avenue serve 5,300 and 5,000 vpd, respectively. The other ramps in this interchange all carry 3,500 vpd or less.

B. Current AM and PM Peak Hour Volumes


AM and PM peak hour traffic counts were collected along I-95, US 322, and several ramps in the study area. In addition, peak hour intersection turning movement counts were taken at the ramp junctions and other key signalized intersections in the study area. These include nine intersections along PA 452, extending from its interchange with I-95 north to Lamp Post Lane. These peak hour volumes are shown in Figure 3.

Along I-95, peak hour volumes range from 4,175 to 5,933 vehicles per hour (vph), with the highest volumes occurring just north of Exit 3 and the lowest occurring just south of Exit 3. Peak hour volumes on US 322 are between 884 and 1,353 vph. These volumes are noticeably higher on the east side of PA 452 compared to the west side. Along PA 452, the highest volumes occur between US 322 and Duttons Mill Road. Duttons Mill Road also has the highest volumes of any of PA 452's intersecting streets, because it is the primary entrance to the Duttons Mill Business Park.


I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 2. Current Average Daily Traffic Volumes

ASTON
 27.6 Current Average Daily Traffic Volumes AADT (000s)




Delaware Valley Regional
 Planning Commission
 March 2008




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 3A. Current AM / PM Peak Hour Traffic Volumes



**I-95 / US 322 INTERCHANGE
TRAFFIC STUDY**

**Figure 3B. Current AM / PM
Peak Hour Traffic Volumes**



[This page intentionally left blank]

III. IMPROVEMENT ALTERNATIVES

Traffic forecasts were prepared and evaluated for the years 2014 and 2034 under four different highway network alternatives: a No-Build and three Build alternatives. For each of these alternatives, DVRPC's travel simulation model was modified to reflect the alternative under consideration and was used to prepare travel forecasts representative of that scenario. The No-Build Alternative provides a useful future-year reference against which any impacts associated with the Build alternatives may be compared and quantified. A graphical depiction of the interchange modifications associated with each of the Build alternatives is provided in Figure 4.

A. No-Build Alternative

The No-Build Alternative does not include any changes to the I-95 / US 322 Interchange. This alternative does, however, include improvements to other regional facilities that are included in DVRPC's Transportation Improvement Program (TIP) and Long Range Plan, and that may have an impact on travel patterns in the study area once they are built. These TIP and Plan projects include the widening of US 322 from US 1 to PA 452 to four lanes, the construction of a new partial interchange between the Commodore Barry Bridge approach and PA 291 to include a US 322 eastbound off-ramp and a westbound on-ramp, and the widening of US 202 from the Delaware State Line to Matlack Street near West Chester Borough. These projects are also included as part of each of the Build alternatives.


B. Build Alternative 1

Build Alternative 1 would relocate I-95 northbound to an alignment adjacent to the I-95 southbound lanes. A new auxiliary roadway would be provided along the existing I-95 northbound alignment. This auxiliary roadway would serve as a collector-distributor road, which would accommodate I-95 northbound traffic exiting to Township Line Road / 15th Street. The existing I-95 northbound on-ramp from Highland Avenue would be relocated to Township Line Road. Both this on-ramp and the ramp from US 322 eastbound to I-95 northbound would join the auxiliary roadway, which would then merge with I-95 northbound traffic. Because this merge would be on the right-hand side of I-95 northbound, the weaving movement from US 322 eastbound to the Commodore Barry Bridge would be eliminated. In addition, a new ramp from US 322 eastbound to I-95 southbound would be constructed.


Additional capacity on I-95 through the interchange area would also be provided. In the northbound direction, I-95 would be widened to four lanes just south of the interchange. The right lane would diverge onto the auxiliary roadway and three I-95 northbound lanes would continue through the interchange. The auxiliary roadway, after picking up Township

I-95 / US 322 INTERCHANGE TRAFFIC STUDY


Figure 4. Proposed Improvements Under Build Alternatives 1, 2, and 3
Build Alternative 1




Build Alternative 2



Build Alternative 3



- Relocated I-95 Northbound
- Proposed Collector - Distributor Road
- Proposed Ramps
- x-x-x-x-x-x- Removed



Line Road and US 322 eastbound traffic, would merge with I-95 as a two-lane ramp. I-95 northbound would drop from five lanes to four just north of Engle Street. An additional lane drop would occur at the northbound off-ramp to the Commodore Barry Bridge interchange at Exit 4.

In the southbound direction, a fourth I-95 lane would be provided from the Commodore Barry Bridge interchange through the off-ramp to Highland Avenue, and then dropped at the off-ramp to US 322 westbound at Exit 3. The southbound on-ramp from Highland Avenue would combine with the new US 322 eastbound to I-95 southbound ramp. This traffic would be given a much greater distance to merge with I-95 southbound traffic, by providing a fourth travel lane for approximately one-half mile beyond the interchange.

C. Build Alternative 2

Build Alternative 2 would also relocate I-95 northbound to an alignment adjacent to the southbound travel lanes. However, no auxiliary roadway would be provided. Rather, a new loop ramp from US 322 eastbound to I-95 northbound with a right-hand merge would be constructed to replace the existing US 322 eastbound left-hand merge with I-95. This loop ramp would split off from the existing US 322 eastbound ramp to Township Line Road. This ramp would be widened to two lanes, with one lane continuing to Township Line Road and the other becoming the new loop ramp. The right-hand merge onto I-95 northbound would eliminate the US 322 eastbound to Commodore Barry Bridge interchange weaving movement.

The I-95 northbound on-ramp from Highland Avenue would remain near its present location, but would be modified to allow westbound Highland Avenue traffic to access the ramp via a left turn. As in Alternative 1, a new US 322 eastbound to I-95 southbound ramp and limited widening of I-95, from approximately one-half mile south of Exit 3 to the vicinity of Engle Street, would also be provided as part of Build Alternative 2.

D. Build Alternative 3

Build Alternative 3, like Alternative 2, would provide a new loop ramp from US 322 eastbound to I-95 northbound. However, the ramp from US 322 eastbound to Township Line Road would be eliminated. This traffic would join I-95 northbound via the new loop ramp and then quickly exit from a new I-95 northbound off-ramp to Highland Avenue. This off-ramp would be across Highland Avenue from a reconstructed I-95 northbound on-ramp, which would be in the same location as the on-ramp from Highland Avenue provided in Build Alternative 2. Build Alternative 3 would also include a new ramp from US 322 eastbound to I-95 southbound. Another new ramp, unique to Alternative 3, would be provided to allow I-95 northbound traffic direct access to US 322 westbound. I-95 mainline widening, similar to that of Build alternatives 1 and 2, would also be provided to maintain

three through travel lanes in each direction through the interchange. In the northbound direction, a fourth lane would be provided between the on-ramp from US 322 eastbound and the off-ramp to Highland Avenue, a distance of approximately 2,000 feet.

IV. TRAVEL FORECASTING PROCEDURES

DVRPC's travel simulation models are used to forecast future travel patterns. These models utilize a system of traffic zones that follow Census boundaries and rely on demographic and employment data, land use, and transportation network characteristics to simulate trip-making patterns throughout the region.

A. Socioeconomic Projections

DVRPC's long-range population and employment forecasts are revised periodically to reflect changing market trends, development patterns, local and national economic conditions, and available data. The completed forecasts reflect all reasonably known current information and the best professional judgement of predicted future conditions. The revised forecasts adopted by the DVRPC Board in February 2005 are an update to municipal forecasts that were last completed in 2000, and form the basis for the forecasts used in this traffic study.

DVRPC uses a multistep, multisource methodology to produce its forecasts at the county level. County forecasts serve as control totals for municipal forecasts, which are disaggregated from county totals. Municipal forecasts are based on an analysis of historical data trends adjusted to account for infrastructure availability, environmental constraints to development, local zoning policy, and development proposals. Municipal population forecasts are constrained using density ceilings and floors. County, and, where necessary, municipal input is used throughout the process to derive the most likely population forecasts for all geographic levels.

1. Population Forecasting

Population forecasting at the regional level involves review and analysis of six major components: births, deaths, domestic in-migration, domestic out-migration, international immigration, and changes in group quarters populations (e.g., dormitories, military barracks, prisons, and nursing homes). DVRPC uses both the cohort survival concept to age individuals from one age group to the next, and a modified Markov transition probability model based on the most recent US Census and the US Census Bureau's recent Current Population Survey (CPS) research, to determine the flow of individuals between the Delaware Valley and areas outside the region. For movement within the region, Census and IRS migration data, coupled with CPS data, are used to determine migration rates between counties. DVRPC relies on county planning offices to provide information on any known, expected, or forecasted changes in group quarters populations. These major population components are then aggregated and the resulting population forecasts are reviewed by member governments for final adjustments based on local knowledge.

2. Employment Forecasting

Employment is influenced by local, national, and global political and socioeconomic factors. The US Census Bureau provides the most reasonable and consistent time series data on county employment by sector, and serves as DVRPC's primary data source for employment forecasting. Employment sectors include mining, agriculture, construction, manufacturing, transportation, wholesale, retail, finance / insurance, service, government, and military. Other supplemental sources of data include the Bureau of Economic Analysis, the Bureau of Labor Statistics, Occupational Privilege tax data, and other public and private sector forecasts. As in the population forecasts, county-level total employment is used as a control total for sector distribution and municipal-level forecasts. Forecasts are then reviewed by member counties for final adjustments based on local knowledge.

3. I-95 / US 322 Interchange Study Area Forecasts

As part of the I-95 / US 322 Interchange Traffic Study, DVRPC staff reviewed its most recent current population and employment estimates, its long-range population and employment forecasts, and all proposed land use developments in the study area. In addition, revised long-range population and employment forecast were being developed while this traffic study was underway. A preliminary set of these forecasts was available for the municipalities in this study area. Based on these data, DVRPC developed municipal-level population and employment forecasts for use as inputs to the traffic simulation models. Table 1 summarizes the population and employment forecasts used in the study.

Currently, there are about 107,800 residents and 37,600 jobs in the greater study area. These values are largely unchanged from 2000 levels. Between 2000 and 2005, the population grew by 3,353 residents and employment declined by about 200 jobs. The population increase was largely driven by Bethel Township, which increased its population by 2,700 residents between 2000 and 2005. All other study-area municipalities were stable in terms of both population and employment, with some showing small gains and others showing small losses. This stability is reflective of a mature area that is largely built out. Population and employment changes result primarily from redevelopment of previously developed areas.

This stability is forecast to continue well into the future. Between 2005 and 2030, the total population in the greater study area is projected to increase by only 2,885 residents to 110,639. This represents an increase of just under three percent from the 2005 value. Four of the 12 municipalities in the study area are forecast to experience small declines in population, while the remainder will experience small increases. The largest increases will occur in Chester City, with 933 new residents, and in Bethel Township, with 868 new residents. Bethel Township will also have the highest relative growth at 9.5 percent.

Table 1. Study Area Population and Employment

Municipality	Population					Employment					
	2000	2005	2015	2030	2005 - 2030 Growth	2000	2005	2015	2030	2005 - 2030 Growth	
					Abs.					Abs.	Pct.
Aston Township	16,205	16,801	16,972	17,194	393	5,720	5,863	6,276	6,814	951	16.2%
Bethel Township	6,420	9,102	9,479	9,970	868	1,015	1,124	1,224	1,355	231	20.6%
Brookhaven Borough	7,985	7,843	7,904	7,984	141	1,953	1,923	2,011	2,125	202	10.5%
Chester City	36,854	37,029	37,127	37,962	933	11,191	11,158	11,965	12,980	1,822	16.3%
Chester Township	4,604	4,501	4,549	4,611	110	1,743	1,686	1,814	2,358	672	39.9%
Eddystone Borough	2,442	2,379	2,364	2,345	-34	2,649	2,505	2,499	2,492	-13	-0.5%
Lower Chichester Township	3,591	3,493	3,483	3,469	-24	865	829	850	876	47	5.7%
Marcus Hook Borough	2,314	2,264	2,276	2,293	29	1,979	1,901	1,858	1,802	-99	-5.2%
Parkside Borough	2,265	2,210	2,223	2,239	29	226	221	218	213	-8	-3.6%
Trainer Borough	1,901	1,860	1,812	1,750	-110	1,135	1,075	1,065	1,152	77	7.2%
Upland Borough	2,977	2,908	2,901	2,892	-16	4,112	4,079	4,051	4,015	-64	-1.6%
Upper Chichester Township	16,842	17,364	17,610	17,930	566	5,192	5,207	5,304	5,641	434	8.3%
Study Area Total	104,400	107,754	108,700	110,639	2,885	37,780	37,571	39,135	41,823	4,252	11.3%

DVRRPC - September 2007

The study area will add 4,252 new jobs between 2005 and 2030, an increase of 11.3 percent. Again, four of the 12 study area municipalities are projected to experience slight declines in employment. Over 40 percent of the study area employment growth will occur in Chester City. This growth will be driven by the new racetrack / casino and other waterfront redevelopment projects. In total, Chester City employment is projected to increase by 16.3 percent over its 2005 level. Chester and Bethel townships will experience higher employment growth in relative terms, at 39.9 and 20.6 percent, respectively. The majority of the remaining new study area jobs will be located in Aston and Upper Chichester townships.

B. DVRPC's Travel Simulation Process

For the I-95 / US 322 Interchange Traffic Study, a focused simulation process was employed. A focused simulation process uses DVRPC's regional simulation models, but includes a more detailed representation of the study area. Local streets not included in the regional network, but of interest in this study, are added to the highway network. Traffic zones inside the study area are subdivided so that traffic from existing and proposed land use developments may be loaded more precisely onto the network. The focusing process increases the accuracy of the travel forecasts within the detailed study area. At the same time, all existing and proposed highways throughout the region, and their impact on both regional and interregional travel patterns, become an integral part of the simulation process.

DVRPC's travel models follow the traditional steps of trip generation, trip distribution, modal split, and traffic assignment. However, an iterative feedback loop is employed from traffic assignment to the trip distribution step. The feedback loop ensures that the congestion levels used by the models when determining trip origins and destinations are equivalent to those that result from the traffic assignment step. Additionally, the iterative model structure allows trip making patterns to change in response to changes in traffic patterns, congestion levels, and improvements to the transportation system.

The DVRPC travel simulation process uses the Evans Algorithm to iterate the model. Evans reexecutes the trip distribution and modal split models based on updated highway speeds after each iteration of highway assignment and assigns a weight to each iteration. This weight is then used to prepare a convex combination of the link volumes and trip tables for the current iteration and a running weighted average of the previous iterations. This algorithm converges rapidly to the equilibrium solution on highway travel speeds and congestion levels. About seven iterations are required for the process to converge to the equilibrium state for study area travel patterns.

The DVRPC travel simulation models are disaggregated into separate peak, midday, and evening time periods. This disaggregation begins in trip generation, where factors are used to separate daily trips into peak, midday, and evening travel. The enhanced process then utilizes completely separate model chains for peak, midday, and evening travel simulation

runs. Time-of-day sensitive inputs to the models, such as highway capacities and transit service levels, are disaggregated to be reflective of time-period-specific conditions. Capacity factors are used to allocate daily highway capacity to each time period. Separate transit networks were used to represent the difference in transit service over the course of a day.

The enhanced model is disaggregated into separate model chains for the peak (combined AM and PM), midday (the period between the AM and PM peaks), and evening (the remainder of the day) periods for the trip distribution, modal split, and travel assignment phases of the process. The peak period is defined as 7:00 AM to 9:00 AM and 3:00 PM to 6:00 PM. Peak period and midday travel are based on a series of factors that determine the percentage of daily trips that occur during those periods. Evening travel is then defined as the residual after peak and midday travel are removed from daily travel. External-local productions at the nine-county cordon stations are disaggregated into peak, midday, and evening components using percentages derived from the temporal distribution of traffic counts taken at each cordon station.


For the I-95 / US 322 Interchange Traffic Study, an additional trip purpose was added to DVRPC's standard travel demand model to represent casino visitor trips. These trips have different characteristics than the other trip purposes in DVRPC's travel demand model. They tend to have a different trip length frequency distribution with a longer average trip length and a somewhat higher average auto occupancy than other trips.

Figure 5 provides a flow chart of the travel demand forecasting process. The first step in the process involves generating the number of trips that are produced by and destined for each traffic zone and cordon station throughout the nine-county region.

1. Trip Generation

Both internal trips (those made within the DVRPC region) and external trips (those that cross the boundary of the region) must be considered in the simulation of regional travel. For the simulation of travel demand, internal trip generation is based on zonal forecasts of population and employment, whereas external trips are extrapolated from cordon line traffic counts and other sources. The latter also include trips that pass through the Delaware Valley region. Estimates of internal trip productions and attractions by zone are established for each trip purpose on the basis of trip rates applied to the zonal estimates of demographic and employment data. Trip purposes include work and nonwork trips, light and heavy truck trips, and taxi trips. This part of the DVRPC model is not iterated on highway travel speed. Rather, estimates of daily trip making by traffic zone are calculated and then disaggregated into peak, midday, and evening time periods.

Figure 5. DVRPC's Travel Modeling Process



EVANS ALGORITHM ONLY

2. Evans Iterations

The iterative portion of the Evans forecasting process involves updating the highway network restrained link travel speeds, rebuilding the minimum time paths through the network, and skimming the interzonal travel time for the minimum paths. Then the trip distribution, modal split, and highway assignment models are executed in sequence for each pass through the model chain. After convergence is reached, the transit trip tables for each iteration are weighted together and the weighted average table is assigned to the transit network. The highway trip tables are loaded onto the network during each Evans iteration. For each time period, seven iterations of the Evans process are performed to ensure that convergence on travel times is reached.

3. Trip Distribution

Trip distribution is the process by which the zonal trip ends established in the trip generation analysis are linked together to form origin-destination patterns in the trip table format. Peak, midday, and evening trip ends are distributed separately. For each Evans iteration, a series of ten gravity-type distribution models are applied at the zonal level. These models follow the trip purpose and vehicle type stratifications established in trip generation.

4. Modal Split

The modal split model is also run separately for the peak, midday, and evening time periods. The modal split model calculates the fraction of each person-trip interchange in the trip table that should be allocated to transit, and then assigns the residual to the highway side. The choice between highway and transit usage is made on the basis of comparative cost, travel time, and frequency of service, with other aspects of modal choice being used to modify this basic relationship. In general, the better the transit service, the higher the fraction assigned to transit, although trip purpose and auto ownership also affect the allocation. The model subdivides highway trips into auto drivers and passengers. Auto driver trips are added to the truck, taxi, and external vehicle trips in preparation for assignment to the highway network.

5. Highway Assignment

For highway trips, the final step in the focused simulation process is the assignment of vehicle trips to the highway network representative of the alternative being modeled. For peak, midday, and evening travel, the assignment model produces the future traffic volumes for individual highway links that are required for the evaluation of each alternative. The regional nature of the highway network and trip table underlying the focused

assignment process allows the diversion of travel into and through the study area to various points of entry and exit in response to the improvements made in the transportation system.

For each Evans iteration, highway trips are assigned to the network representative of a given alternative by determining the best (minimum time) route through the highway network for each zonal interchange, and then allocating the interzonal highway travel to the highway facilities along that route. This assignment model is "capacity restrained," which means that congestion levels are considered when determining the best route. The Evans equilibrium assignment method is used to implement the capacity constraint. When the assignment and associated trip table reach equilibrium, no path faster than the one actually assigned for each trip can be found through the network, given the capacity restrained travel times on each link.

6. Transit Assignment

After equilibrium is achieved, the weighted average transit trip tables are assigned to the transit network to produce link and route passenger volumes. The transit person trips produced by the modal split model are "linked," which means that they do not include any transfers that occur either between transit trips or between auto approaches and transit lines. The transit assignment procedure accomplishes two major tasks. First, the transit trips are "unlinked" to include transfers, and second, the unlinked transit trips are associated with specific transit facilities to produce link, line, and station volumes. These tasks are accomplished simultaneously within the transit assignment model, which assigns the transit trip matrix to minimum impedance paths built through the transit network. There is no capacity-restraining procedure in the transit assignment model.

C. Highway Traffic Assignment Validation

Before a focused simulation model can be used to predict future trip making patterns, its ability to replicate existing conditions is tested. The simulated highway assignment outputs are compared to current traffic counts taken on roadways serving the study area. The focused simulation model was executed with current conditions and the results were compared with recent traffic counts. Based on this analysis, the focused model produced accurate traffic volumes. The validated model was then executed for the No-Build and each Build alternative, with socioeconomic and land use inputs reflective of future conditions and the specific alternative under evaluation.

A total of 73 locations throughout the greater study area with available daily traffic counts were used for model validation. Eight of these locations are along I-95; five are on US 322; 38 are on either I-95 or US 322 interchange ramps; and 22 are on other facilities, such as PA 452, Highland Avenue, Township Line Road, and PA 291. The total assigned traffic on all facilities, 1.59 million vehicles, is within six percent of the total counted volume of 1.62 million vehicles.

V. PROJECTED TRAFFIC VOLUMES


Projected traffic volumes for the anticipated opening year, 2014, and a horizon year of 2034 are presented and analyzed in this chapter. Daily and peak hour forecasts for the No-Build and three Build alternatives are presented. For each alternative, a focused 2030 trip table was prepared by disaggregating the zonal demographic and employment inputs to the trip generation model and executing the DVRPC travel model through traffic assignment. The resulting travel matrix includes all travel patterns throughout the Delaware Valley region, including trips entering and exiting the region at its cordon. Traffic volumes for 2014 were developed by interpolating between the current and 2030 trip tables. Volumes for 2034 were found by extrapolating the trend between the current and 2030 traffic patterns to 2034.

Estimates of future year AM and PM peak hour volumes, including intersection turning movements, were calculated by scaling current peak hour volumes according to growth factors on each link and intersection leg. These growth factors represent the ratio of future year peak hour link volumes to current year peak hour volumes. The future year peak hour volumes for each link and intersection leg were determined by multiplying the forecasted AADT by directional AM and PM peak hour “K” factors. Existing “K” factors were calculated from traffic counts as the ratio of the highest morning and evening hourly volumes to the total AADT. Future year “K” factors were based on the existing “K” factors and the AADT growth on each intersection approach, accounting for the “peak spreading” that typically occurs as daily traffic volumes and congestion levels increase. The resulting forecasted AM and PM link volumes and intersection turning movements were adjusted as necessary to balance traffic flows between adjacent interchanges and intersections.

A. 2014 Daily Traffic Forecasts


Figure 6 provides the 2014 average daily traffic volumes for the No-Build Alternative, along with the current traffic volumes for comparison. In the figure, current traffic volumes are shown in black, underneath the line representing the highway links; No-Build volumes are shown in red, just above the line.

Under the No-Build Alternative, 2014 volumes on I-95 in the study area range from 115,800 to 155,100 vehicles per day (vpd), representing increases of 5,600 to 9,200 vpd over current volumes. US 322 volumes are approximately 5,000 vpd higher than current volumes and range from 32,500 to 38,300 west of I-95. This growth is largely a result of the US 322 widening from US 1 to PA 452, which is included in the future highway networks. East of I-95, at the Commodore Barry Bridge interchange, US 322 carries 40,500 vpd in 2014 under the No-Build Alternative. PA 452 volumes increase by 1,100 to 1,300 vpd; 2014 traffic volumes are between 17,900 and 25,100 vpd. Individual ramps within the I-95 / US 322 interchange increase by 400 to 2,000 vpd. The largest increases



I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Inset 6A. Current and 2014 No-Build Alternative Average Daily Traffic Volumes



occur on the US 322 eastbound to I-95 northbound ramp and on the reverse movement from I-95 southbound to US 322 westbound. All other ramps increase by 700 vpd or less.

Figure 7 displays the 2014 daily traffic forecasts for the three Build alternatives, along with the corresponding No-Build volume for comparison. Along I-95, average daily traffic volumes under the No-Build and all three Build alternatives are very similar. Build Alternative 1 increases volumes by 0 to 500 vpd, compared to the No-Build Alternative, while Build Alternative 2 increases I-95 volumes by 100 to 300 vpd. Build Alternative 3 volumes along I-95 are between 700 vpd lower and 1,500 vpd higher than the No-Build Alternative volumes.

The largest differences occur on either side of the I-95 / PA 452 interchange. The proposed ramps between US 322 eastbound and I-95 southbound in all of the Build alternatives and between I-95 northbound and US 322 westbound in Build Alternative 3 change traffic patterns between I-95, US 322, and PA 452. Absent these ramps, some motorists use the I-95 / PA 452 interchange to make the connections that are currently not served at the I-95 / US 322 interchange.

West of I-95, US 322 volumes increase by 2,300 to 2,900 vpd under the various Build alternatives, compared to the corresponding No-Build volume. Daily traffic volumes under Build alternatives 1 and 2 are essentially identical; Build Alternative 3 volumes are 300 to 500 vpd higher than the Alternative 1 / Alternative 2 volume. PA 452 volumes are reduced by 300 to 1,000 vpd compared to the No-Build Alternative.


The proposed ramp from US 322 eastbound to I-95 southbound carries 1,800 vpd in 2014 under all three Build alternatives. The proposed ramp from I-95 northbound to US 322 westbound in Build Alternative 3 also carries 1,800 vpd in 2014. The I-95 northbound on-ramp from Highland Avenue or Township Line Road also carries the same volume under each of the Build alternatives, 5,800 vpd, which is 200 vpd higher than the No-Build volume. This increase is due to the enhanced ability of eastbound Highland Avenue traffic to access this ramp under the Build alternatives. This ramp can only be accessed via Highland Avenue westbound in the current and No-Build configurations.

Table 2 provides a summary of the current and 2014 average daily traffic volumes under the No-Build and Build alternatives. The table includes absolute and relative differences between current and No-Build volumes and between No-Build and Build alternative volumes.

I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 7: 2014 No-Build and Build Alternatives 1, 2, and 3 Average Daily Traffic Volumes

- 35.1 2014 Build Alternative 3 AADT (000s)
- 34.8 2014 Build Alternative 2 AADT (000s)
- 34.3 2014 Build Alternative 1 AADT (000s)
- 32.5 2014 No-Build Alternative AADT (000s)



I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Inset 7A. 2014 No-Build Alternative and Build Alternative 1 Average Daily Traffic Volumes



0 500 1,000 1,500 2,000 Feet




Delaware Valley Regional
Planning Commission
March 2008

2014 Build Alternative 1 AADT (000s) 9.8
2014 No-Build Alternative AADT (000s) 9.7

x x x x x x x x

I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Inset 7B. 2014 No-Build Alternative and Build Alternative 2 Average Daily Traffic Volumes



I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Inset 7C. 2014 No-Build Alternative and Build Alternative 3 Average Daily Traffic Volumes




Table 2. Current and 2014 Average Daily Traffic Volumes

Location	Current Counts	2014 Forecast		2014 Forecast		2014 Forecast		2014 Forecast		2014 Forecast		
		No-Build	Current - 2014 Change Absolute	Alternative 1	Build / No-Build Diff Absolute	Alternative 2	Alt 2 / Alt 1 Diff Absolute	Alternative 3	Alt 3 / Alt 1 Diff Absolute	Alternative 1	Alternative 2	Alternative 3
		Percent	Percent	Percent	Percent	Percent	Percent	Percent	Percent	Percent	Percent	
<i>Interstate 95 Mainline</i>												
Delaware State Line to Chichester Avenue	110,200	5,600	5.1%	116,000	200	0.2%	115,900	-100	-0.1%	115,500	-500	-0.4%
Chichester Avenue to PA 452 (Market Street)	110,480	5,920	5.4%	116,700	300	0.3%	116,500	-200	-0.2%	115,700	-1,000	-0.9%
PA 452 (Market Street) to US 322 (Conchester Road)	112,100	6,000	5.4%	118,600	500	0.4%	118,400	-200	-0.2%	119,600	1,000	0.8%
US 322 (Conchester Road) to US 322 (Commodore Barry Bridge)	145,890	9,210	6.3%	155,200	100	0.1%	155,200	0	0.0%	154,900	-300	-0.2%
US 322 (Commodore Barry Bridge) to Kerlin Street	132,250	7,850	5.9%	140,100	0	0.0%	140,200	100	0.1%	140,200	0	0.1%
Kerlin Street to PA 352 (Edgemont Ave)	133,983	8,217	6.1%	142,300	100	0.1%	142,400	100	0.1%	142,400	100	0.1%
<i>Interstate 95 Ramps</i>												
I-95 Northbound Off-Ramp to PA 452	4,000	300	7.5%	4,300	0	0.0%	4,300	0	0.0%	3,000	-1,300	-30.2%
I-95 Northbound On-Ramp from PA 452	5,280	320	6.1%	5,700	100	1.8%	5,700	0	0.0%	5,800	100	1.8%
I-95 Southbound On-Ramp from PA 452	4,800	310	6.6%	4,800	-200	-4.0%	4,800	0	0.0%	4,200	-600	-12.5%
I-95 Southbound Off-Ramp to PA 452	5,030	370	7.4%	5,300	-100	-1.9%	5,300	0	0.0%	5,300	0	0.0%
I-95 Northbound Off-Ramp to Township Line Road / C-D Road	3,600	680	23.3%	3,500	-100	-2.8%	3,300	-200	-5.7%	4,300	800	22.9%
I-95 Northbound On-Ramp from US 322 Eastbound	13,770	2,030	14.7%	16,200	400	2.9%	16,200	0	0.0%	17,500	1,300	8.0%
I-95 Northbound On-Ramp from Highland Ave/2wp Line/CD Road	5,040	560	11.1%	5,800	200	3.6%	5,800	0	0.0%	5,800	0	0.0%
I-95 Northbound Off-Ramp to US 322 WB	0	0	----	0	0	----	0	0	----	1,800	1,800	----
I-95 Southbound On-Ramp from US 322 EB	0	0	----	1,800	1,800	----	1,800	0	0.0%	1,800	0	0.0%
I-95 Southbound On-Ramp from Highland Ave/Bethel Road	3,520	380	10.8%	3,600	-300	-7.7%	3,600	0	0.0%	3,600	0	0.0%
I-95 Southbound Off-Ramp to US 322 WB	16,100	1,300	8.1%	17,700	300	1.7%	17,700	0	0.0%	17,700	0	0.0%
I-95 Southbound Off-Ramp to Highland Avenue	5,320	380	7.1%	5,800	100	1.8%	5,800	0	0.0%	5,800	0	0.0%
I-95 Northbound Off-Ramp to US 322 EB (Comm Barry Bridge)	8,580	1,120	13.1%	9,800	100	1.0%	9,800	0	0.0%	9,800	0	0.0%
I-95 Northbound On-Ramp from US 322 WB (Comm Barry Bridge)	9,400	1,200	12.8%	10,700	100	0.9%	10,700	0	0.0%	10,800	100	0.9%
I-95 Southbound On-Ramp from US 322 WB (Comm Barry Bridge)	7,520	800	13.0%	8,600	100	1.2%	8,600	-100	-1.2%	8,400	-200	-2.3%
I-95 Southbound On-Ramp from Kerlin Street C-D Road	6,940	460	6.6%	7,400	0	0.0%	7,400	0	0.0%	7,300	-100	-1.4%
I-95 Southbound Off-Ramp to Kerlin Street C-D Road	7,400	800	10.8%	8,300	100	1.2%	8,300	0	0.0%	8,300	0	0.0%
I-95 Northbound Off-Ramp to Kerlin Street	5,667	433	7.6%	6,100	0	0.0%	6,100	0	0.0%	6,100	0	0.0%
I-95 Northbound Off-Ramp to Edgemont Avenue	4,207	393	9.3%	4,600	0	0.0%	4,600	0	0.0%	4,600	0	0.0%
I-95 Southbound On-Ramp from Edgemont Avenue	3,301	399	12.1%	3,700	0	0.0%	3,700	0	0.0%	3,600	-100	-2.7%
<i>US 322 Mainline</i>												
West of PA 452 Interchange	27,610	4,890	17.7%	34,800	2,300	7.1%	34,800	0	0.0%	35,100	300	0.9%
PA 452 Interchange to Bethel Road Interchange	33,200	4,900	14.8%	40,500	2,400	6.3%	40,500	0	0.0%	41,000	500	1.2%
Bethel Road Interchange to Interstate 95	33,430	4,870	14.6%	40,700	2,400	6.3%	40,700	0	0.0%	41,200	500	1.2%
Interstate 95 to 9th Street	35,427	5,073	14.3%	40,700	200	0.5%	40,600	-100	-0.2%	40,600	-100	-0.2%
<i>US 322 Ramps</i>												
US 322 Eastbound Off-Ramp to PA 452 Southbound	1,270	330	26.0%	1,500	-100	-6.3%	1,500	0	0.0%	1,400	-100	-6.7%
US 322 Eastbound On-Ramp from PA 452 Southbound	2,950	350	11.9%	3,300	0	0.0%	3,300	0	0.0%	3,300	0	0.0%
US 322 Eastbound Off-Ramp to PA 452 Northbound	1,040	360	34.6%	1,400	0	0.0%	1,400	0	0.0%	1,400	0	0.0%
US 322 Eastbound On-Ramp from PA 452 Northbound	820	280	34.1%	1,100	0	0.0%	1,100	0	0.0%	1,100	0	0.0%
US 322 Westbound On-Ramp from PA 452 Southbound	760	240	31.6%	1,000	0	0.0%	1,000	0	0.0%	1,000	0	0.0%
US 322 Westbound Off-Ramp to PA 452 Southbound	2,070	230	11.1%	2,300	0	0.0%	2,300	0	0.0%	2,200	-100	-4.3%
US 322 Westbound On-Ramp from PA 452 Northbound	400	200	50.0%	600	0	0.0%	600	0	0.0%	400	-200	-33.3%
US 322 Westbound Off-Ramp to PA 452 Northbound	3,220	280	8.7%	3,500	0	0.0%	3,500	0	0.0%	3,500	0	0.0%

Table 2. Current and 2014 Average Daily Traffic Volumes

Location	Current Counts	2014 Forecast		2014 Forecast		2014 Forecast		2014 Forecast		2014 Forecast		2014 Forecast			
		No-Build	Current - 2014 Change	Alternative 1	Build / No-Build Diff	Alternative 2	Alt 2 / Alt 1 Diff	Alternative 3	Alt 3 / Alt 1 Diff	Alternative 1	Build / No-Build Diff	Alternative 2	Alt 2 / Alt 1 Diff	Alternative 3	Alt 3 / Alt 1 Diff
		Absolute	Percent	Absolute	Absolute	Percent	Absolute	Percent	Absolute	Percent	Absolute	Percent	Absolute	Percent	
US 322 Eastbound Off-Ramp to Bethel Road	780	900	15.4%	900	0	0.0%	900	0	0.0%	900	0	0.0%	1,000	100	11.1%
US 322 Eastbound On-Ramp from Bethel Road	910	1,100	20.9%	1,100	0	0.0%	1,100	0	0.0%	1,100	0	0.0%	1,100	0	0.0%
US 322 Westbound On-Ramp from Bethel Road	260	500	92.3%	240	0	0.0%	500	0	0.0%	500	0	0.0%	400	-100	-20.0%
US 322 Westbound Off-Ramp to Bethel Road	360	500	38.9%	140	0	0.0%	500	0	0.0%	500	0	0.0%	500	0	0.0%
US 322 Eastbound Off-Ramp to Township Line Road	1,910	2,600	36.1%	690	0	0.0%	2,600	0	0.0%	2,600	0	0.0%	0	-2,600	-100.0%
US 322 Westbound On-Ramp from Highland Avenue	1,760	2,500	42.0%	740	-100	-4.0%	2,400	-100	-4.0%	2,400	0	0.0%	2,400	0	0.0%
US 322 Westbound Off-Ramp to Bethel Road	1,390	1,700	22.3%	310	-100	-5.9%	1,600	-100	-5.9%	1,600	0	0.0%	1,600	0	0.0%
US 322 Eastbound On-Ramp from I-95 SB and Kerlin St	8,151	10,000	22.7%	1,849	0	0.0%	10,000	0	0.0%	10,000	0	0.0%	10,000	0	0.0%
<i>Other Facilities</i>															
PA 452 West of Dutton Mill Road	17,487	18,700	6.9%	1,213	-400	-2.1%	18,300	-400	-2.1%	18,300	0	0.0%	18,300	0	0.0%
PA 452 from Dutton Mill Road to Bethel Road	23,560	24,900	5.7%	1,340	-400	-1.6%	24,500	-400	-1.6%	24,400	-100	-0.4%	24,200	-300	-1.2%
PA 452 from Bethel Road to Interstate 95	23,560	25,100	6.5%	1,540	-500	-2.0%	24,600	-500	-2.0%	24,600	0	0.0%	24,100	-500	-2.0%
PA 452 South of Interstate 95	16,758	17,900	6.8%	1,142	-300	-1.7%	17,600	-300	-1.7%	17,500	-100	-0.6%	17,200	-400	-2.3%
Bethel Road from US 322 to Highland Avenue	4,291	5,200	21.2%	909	-100	-1.9%	5,100	-100	-1.9%	5,100	0	0.0%	5,100	0	0.0%
Bethel Road from Highland Avenue to Concord Road	8,623	10,100	17.1%	1,477	0	0.0%	10,100	0	0.0%	10,100	0	0.0%	10,100	0	0.0%
Highland Avenue from I-95 NB Ramps to I-95 SB Ramps	12,381	13,100	5.8%	719	100	0.8%	13,200	100	0.8%	13,300	100	0.8%	14,300	1,000	8.3%
Highland Avenue from I-95 NB Ramps to Twp Line Rd (15th St)	12,016	12,800	6.5%	784	-3,700	-28.9%	9,100	-3,700	-28.9%	12,600	3,500	38.5%	13,500	4,400	48.4%
Highland Avenue from Twp Rd (15th St) to US 13 (9th St)	14,281	15,000	5.0%	719	-300	-2.0%	14,700	-300	-2.0%	14,800	100	0.7%	14,800	100	0.7%
Highland Avenue from US 13 (9th St) to PA 291 (2nd St)	7,652	8,200	7.2%	548	-200	-2.4%	8,000	-200	-2.4%	8,000	0	0.0%	8,100	100	1.3%
Township Line Road (15th St) from US 322 Ramp to Highland Ave.	9,751	10,500	7.7%	749	-100	-1.0%	10,400	-100	-1.0%	10,200	-200	-1.9%	5,300	-5,100	-49.0%

B. 2014 AM and PM Peak Hour Traffic Forecasts

AM and PM peak hour traffic forecasts for 2014 under the No-Build Alternative are shown in Figure 8. Along I-95, peak hour volumes range from 4,430 to 6,100 vehicles per hour (vph). These volumes represent increases from less than 100 to more than 400 vph over current peak hour volumes. The highest volumes occur just north of Exit 3. This is also the location with the greatest increase over current traffic volumes. The lowest volumes continue to occur just south of Exit 3.

Peak hour volumes on US 322 are between 1,050 and 1,500 vph west of I-95. Higher volumes occur on US 322 east of I-95 on the approach to the Commodore Barry Bridge. Here, 2014 peak hour volumes under the No-Build Alternative range from 1,570 to 2,480 vph. Peak hour ramp volumes also increase throughout the study area. However, few ramps increase by more than 100 vph over current volumes.


Peak hour volumes along PA 452 increase by more than 100 vph at several locations; however, most individual vehicle movements increase by less than 100 vph. No left- or right-turning volume increases by 100 vph or more, although some eastbound through movements do increase by 100 vph or more during both the AM and PM peak hours.

Peak hour traffic volumes in 2014 under Build Alternative 1 tend to be slightly higher than the corresponding No-Build volumes along both I-95 and US 322. The most significant differences occur on US 322 eastbound as it approaches the I-95 interchange at Exit 3. The provision of a new eastbound ramp to I-95 southbound increases both AM and PM peak hour volumes by approximately 200 vph. The relocation of the I-95 northbound on-ramp from Highland Avenue to Township Line Road changes traffic patterns in the vicinity of the Highland Avenue / 15th Street intersection. Peak Hour traffic volumes on most other study area facilities, including PA 452, are largely unchanged from the No-Build Alternative. Figure 9 provides the 2014 AM and PM peak hour traffic forecasts under Build Alternative 1.

Build Alternative 2 peak hour volumes are very similar to the Build Alternative 1 peak hour volumes, and are slightly higher than the corresponding No-Build Alternative volumes. Both the AM and PM peak hour traffic volumes from US 322 eastbound to I-95 southbound, I-95 northbound, and Township Line Road / 15th Street are the same. Other ramps within the I-95 / US 322 interchange are also within 10 vph of the Build Alternative 1 traffic volumes. The only significant differences are in the area of Highland Avenue, Township Line Road, and 15th Street, which is due to the different configuration of ramps in this area under Build Alternative 2. Figure 10 displays the 2014 AM and PM peak hour traffic forecasts for Build Alternative 2.


I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 8A. 2014 No-Build Alternative AM / PM Peak Hour Traffic Volumes




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 8B. 2014 No-Build Alternative AM / PM Peak Hour Traffic Volumes




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 9A. 2014 Build Alternative 1 AM / PM Peak Hour Traffic Volumes




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 9B. 2014 Build Alternative 1
AM / PM Peak Hour Traffic Volumes




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 10A. 2014 Build Alternative 2 AM / PM Peak Hour Traffic Volumes



I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 10B. 2014 Build Alternative 2
AM / PM Peak Hour Traffic Volumes



Peak hour traffic volumes in 2014 under Build Alternative 3 are higher than either of the other Build alternatives at most locations along I-95. These differences are 90 vph or less. When compared to the No-Build Alternative, they are as much as 130 vph. The largest differences occur in the northbound direction, just south of the I-95 / US 322 interchange at Exit 3. These higher volumes are due to the proposed ramp from I-95 northbound to US 322 westbound under Build Alternative 3. This ramp also increases US 322 westbound volumes, compared to the other Build alternatives. US 322 westbound volumes between I-95 and Bethel Road are 140 vph higher than Build Alternative 1 and Build Alternative 2 volumes in both the AM and PM peak hours. They are also 180 to 190 vph higher than the corresponding volumes under the No-Build Alternative.

Build Alternative 3 combines the I-95 northbound and US 322 eastbound movements to Township Line Road / Highland Avenue onto a single off-ramp exiting at Highland Avenue. This results in significantly less traffic on Township Line Road and 15th Street, but more traffic on Highland Avenue west of 15th Street. Peak hour traffic volumes on most other study area facilities, including PA 452, are largely unchanged from the other Build alternatives. Figure 11 provides the 2014 AM and PM peak hour traffic forecasts under Build Alternative 3.

C. 2034 Daily Traffic Forecasts


The 2034 daily traffic forecasts generally follow the same patterns as the 2014 daily traffic forecasts, except that the differences are more pronounced. The 2034 No-Build Alternative volumes are significantly higher than the 2014 volumes, and the differences between Build and No-Build Alternative volumes and between the three Build alternatives are also greater. Table 3 provides the 2034 average daily traffic volumes under the No-Build and Build alternatives. The table includes absolute and relative differences between current and No-Build volumes and between No-Build and Build alternative volumes.

Figure 12 displays the 2034 average daily traffic volumes in the study area for the No-Build Alternative. The current volumes are also shown for comparison. Under the No-Build Alternative, 2034 volumes on I-95 in the study area will range from 126,300 to 172,400 vpd, representing increases of 14.6 to 18.2 percent over current levels. South of the I-95 / US 322 interchange, daily volumes are forecast to be 16,100 to 17,200 vpd higher than current volumes. Just north of the interchange, No-Build volumes will be 26,500 vpd higher than existing volumes. Once north of the Commodore Barry Bridge interchange at Exit 4, 2034 No-Build Alternative volumes will be 22,500 to 23,800 vpd higher than current volumes.

US 322 volumes will range from 41,800 to 47,400 vpd west of I-95 and will be 50,800 vpd east of Exit 4. These volumes represent increases of 14,000 to 15,400 vpd over current levels, or 41.8 to 51.4 percent growth. PA 452 volumes are forecast to be between 20,100 and 27,900 vpd. These increases range from 3,300 to 4,300 vpd, or 15.9 to 19.9 percent, over current traffic volumes.

I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 11A. 2014 Build Alternative 3 AM / PM Peak Hour Traffic Volumes



I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 11B. 2014 Build Alternative 3
AM / PM Peak Hour Traffic Volumes





Table 3. Current and 2034 Average Daily Traffic Volumes

Location	Current Counts	2034 Forecast		2034 Forecast		2034 Forecast		2034 Forecast		2034 Forecast			
		No-Build	Current - 2034 Change Absolute	Alternative 1	Build / No-Build Diff Absolute	Alternative 2	Alt 2 / Alt 1 Diff Absolute	Alternative 3	Alt 3 / Alt 1 Diff Absolute	Percent	Percent		
<i>Interstate 95 Mainline</i>													
Delaware State Line to Chichester Avenue	110,200	126,300	16,100	14.6%	126,800	500	0.4%	126,700	-100	-0.1%	127,100	300	0.2%
Chichester Avenue to PA 452 (Market Street)	110,480	127,500	17,020	15.4%	128,100	600	0.5%	127,800	-300	-0.2%	128,400	300	0.2%
PA 452 (Market Street) to US 322 (Conchester Road)	112,100	129,300	17,200	15.3%	130,500	1,200	0.9%	130,100	-400	-0.3%	133,400	2,900	2.2%
US 322 (Conchester Road) to US 322 (Commodore Barry Bridge)	145,890	172,400	26,510	18.2%	172,900	500	0.3%	172,700	-200	-0.1%	172,700	-200	-0.1%
US 322 (Commodore Barry Bridge) to Kerlin Street	132,250	154,800	22,550	17.1%	154,900	100	0.1%	155,000	100	0.1%	155,300	400	0.3%
Kerlin Street to PA 352 (Edgemont Ave)	133,983	157,800	23,817	17.8%	158,000	200	0.1%	158,100	100	0.1%	158,300	300	0.2%
<i>Interstate 95 Ramps</i>													
I-95 Northbound Off-Ramp to PA 452	4,000	4,900	900	22.5%	4,900	0	0.0%	4,900	0	0.0%	3,200	-1,700	-34.7%
I-95 Northbound On-Ramp from PA 452	5,280	6,300	1,020	19.3%	6,500	200	3.2%	6,500	0	0.0%	6,700	200	3.1%
I-95 Southbound On-Ramp from PA 452	4,690	5,600	910	19.4%	5,100	-500	-8.9%	5,100	0	0.0%	4,400	-700	-13.7%
I-95 Southbound Off-Ramp to PA 452	5,030	6,000	970	19.3%	5,900	-100	-1.7%	5,800	-100	-1.7%	5,900	0	0.0%
I-95 Northbound Off-Ramp to Township Line Road / C-D Road	2,920	4,900	1,980	67.8%	4,800	-100	-2.0%	4,400	-400	-8.3%	7,500	2,700	56.3%
I-95 Northbound On-Ramp from US 322 Eastbound	13,770	19,700	5,930	43.1%	20,200	500	2.5%	20,100	-100	-0.5%	23,500	3,300	16.3%
I-95 Northbound On-Ramp from Highland Ave/2wp Line/CD Road	5,040	6,500	1,460	29.0%	7,100	600	9.2%	7,100	0	0.0%	7,000	-100	-1.4%
I-95 Northbound Off-Ramp to US 322 WB	0	0	0	----	0	0	----	0	0	----	2,900	2,900	----
I-95 Southbound On-Ramp from US 322 EB	0	0	0	----	2,700	2,700	----	2,700	0	0.0%	2,900	200	7.4%
I-95 Southbound On-Ramp from Highland Ave/Bethel Road	3,520	4,600	1,080	30.7%	4,200	-400	-8.7%	4,200	0	0.0%	4,300	100	2.4%
I-95 Southbound Off-Ramp to US 322 WB	16,100	19,900	3,800	23.6%	20,400	500	2.5%	20,200	-200	-1.0%	20,100	-300	-1.5%
I-95 Southbound Off-Ramp to Highland Avenue	5,320	6,500	1,180	22.2%	6,400	-100	-1.5%	6,500	100	1.6%	6,300	-100	-1.6%
I-95 Northbound Off-Ramp to US 322 EB (Comm Barry Bridge)	8,580	11,800	3,220	37.5%	12,200	400	3.4%	12,100	-100	-0.8%	12,200	0	0.0%
I-95 Northbound On-Ramp from US 322 WB (Comm Barry Bridge)	9,400	12,900	3,500	37.2%	13,200	300	2.3%	13,200	-200	-1.5%	13,200	0	0.0%
I-95 Southbound On-Ramp from US 322 WB (Comm Barry Bridge)	7,520	10,400	2,880	38.3%	10,700	300	2.9%	10,400	-300	-2.8%	10,200	-500	-4.7%
I-95 Southbound On-Ramp from Kerlin Street C-D Road	6,940	8,300	1,360	19.6%	8,300	0	0.0%	8,200	-100	-1.2%	8,200	-100	-1.2%
I-95 Southbound Off-Ramp to Kerlin Street C-D Road	7,400	9,800	2,400	32.4%	9,900	100	1.0%	9,900	0	0.0%	9,900	0	0.0%
I-95 Northbound Off-Ramp to Kerlin Street	5,667	6,800	1,133	20.0%	6,800	0	0.0%	6,800	0	0.0%	6,900	100	1.5%
I-95 Northbound Off-Ramp to Edgemont Avenue	4,207	5,400	1,193	28.4%	5,400	0	0.0%	5,400	0	0.0%	5,500	100	1.9%
I-95 Southbound On-Ramp from Edgemont Avenue	3,301	4,500	1,199	36.3%	4,500	0	0.0%	4,500	0	0.0%	4,500	0	0.0%
<i>US 322 Mainline</i>													
West of PA 452 Interchange	27,610	41,800	14,190	51.4%	44,900	3,100	7.4%	44,800	-100	-0.2%	46,700	1,800	4.0%
PA 452 Interchange to Bethel Road Interchange	33,200	47,400	14,200	42.8%	50,800	3,400	7.2%	50,600	-200	-0.4%	53,200	2,400	4.7%
Bethel Road Interchange to Interstate 95	33,430	47,400	13,970	41.8%	50,800	3,400	7.2%	50,600	-200	-0.4%	53,100	2,300	4.5%
Interstate 95 to 9th Street	35,427	50,800	15,373	43.4%	51,500	700	1.4%	50,900	-600	-1.2%	51,400	-100	-0.2%
<i>US 322 Ramps</i>													
US 322 Eastbound Off-Ramp to PA 452 Southbound	1,270	2,200	930	73.2%	2,000	-200	-9.1%	2,100	100	5.0%	1,700	-300	-15.0%
US 322 Eastbound On-Ramp from PA 452 Southbound	2,950	3,900	950	32.2%	4,000	100	2.6%	4,000	0	0.0%	4,000	0	0.0%
US 322 Eastbound Off-Ramp to PA 452 Northbound	1,040	2,000	960	92.3%	2,000	0	0.0%	2,000	0	0.0%	2,000	0	0.0%
US 322 Eastbound On-Ramp from PA 452 Northbound	820	1,700	880	107.3%	1,700	0	0.0%	1,700	0	0.0%	1,600	-100	-5.9%
US 322 Westbound On-Ramp from PA 452 Southbound	760	1,500	740	97.4%	1,500	0	0.0%	1,500	0	0.0%	1,500	0	0.0%
US 322 Westbound Off-Ramp to PA 452 Southbound	2,070	2,600	530	25.6%	2,600	0	0.0%	2,600	0	0.0%	2,500	-100	-3.8%
US 322 Westbound On-Ramp from PA 452 Northbound	400	900	500	125.0%	900	0	0.0%	900	0	0.0%	500	-400	-44.4%
US 322 Westbound Off-Ramp to PA 452 Northbound	3,220	4,000	780	24.2%	4,000	0	0.0%	4,000	0	0.0%	4,100	100	2.5%


Table 3. Current and 2034 Average Daily Traffic Volumes

Location	Current Counts	2034 Forecast		2034 Change		2034 Forecast		2034 Forecast		2034 Forecast		2034 Forecast		2034 Forecast				
		No-Build	Build	Absolute	Percent	Alternative 1	Build / No-Build Diff Absolute	Alternative 2	Alternative 3	Alt 2 / Alt 1 Diff Absolute	Alt 3 / Alt 1 Diff Absolute	Alternative 1	Alternative 2	Alternative 3	Alt 2 / Alt 1 Diff Percent	Alt 3 / Alt 1 Diff Percent		
US 322 Eastbound Off-Ramp to Bethel Road	780	1,200	420	53.8%	1,200	0	1,200	0	1,200	0	1,200	0	1,200	0	0.0%	0.0%	300	25.0%
US 322 Eastbound On-Ramp from Bethel Road	910	1,300	390	42.9%	1,300	0	1,300	0	1,300	0	1,300	0	1,300	0	0.0%	0.0%	0	0.0%
US 322 Westbound On-Ramp from Bethel Road	260	800	540	207.7%	800	0	800	0	800	0	800	0	800	0	0.0%	0.0%	-200	-25.0%
US 322 Westbound Off-Ramp to Bethel Road	360	700	340	94.4%	700	0	700	0	700	0	700	0	700	0	0.0%	0.0%	0	0.0%
US 322 Eastbound Off-Ramp to Township Line Road	1,910	4,000	2,090	109.4%	3,800	-200	3,800	-5.0%	3,800	100	3,900	100	3,900	100	2.6%	2.6%	0	-100.0%
US 322 Westbound On-Ramp from Highland Avenue	1,760	3,800	2,040	115.9%	3,700	-100	3,700	-2.6%	3,700	0	3,700	0	3,700	0	0.0%	0.0%	0	0.0%
US 322 Westbound Off-Ramp to Bethel Road	1,390	2,400	1,010	72.7%	1,900	-500	1,900	-20.8%	1,900	0	1,900	0	1,900	0	0.0%	0.0%	200	10.5%
US 322 Eastbound On-Ramp from I-95 SB and Kerlin St	8,151	13,300	5,149	63.2%	13,500	200	13,500	1.5%	13,500	0	13,500	0	13,500	0	0.0%	0.0%	200	1.5%
<i>Other Facilities</i>																		
PA 452 West of Dutton Mill Road	17,487	20,900	3,413	19.5%	19,800	-1,100	19,800	-5.3%	19,800	100	19,900	100	19,900	100	0.5%	0.5%	100	0.5%
PA 452 from Dutton Mill Road to Bethel Road	23,560	27,300	3,740	15.9%	26,200	-1,100	26,200	-4.0%	26,200	-100	26,100	-100	26,300	100	0.4%	0.4%	100	0.4%
PA 452 from Bethel Road to Interstate 95	23,560	27,900	4,340	18.4%	26,500	-1,400	26,500	-5.0%	26,500	-100	26,400	-100	25,900	-600	-2.3%	-2.3%	-600	-2.3%
PA 452 South of Interstate 95	16,758	20,100	3,342	19.9%	19,200	-900	19,200	-4.5%	19,200	-200	19,000	-200	19,000	-200	-1.0%	-1.0%	-200	-1.0%
Bethel Road from US 322 to Highland Avenue	4,291	6,800	2,509	58.5%	6,600	-200	6,600	-2.9%	6,600	0	6,600	0	6,600	0	0.0%	0.0%	0	0.0%
Bethel Road from Highland Avenue to Concord Road	8,623	12,800	4,177	48.4%	12,700	-100	12,700	-0.8%	12,700	0	12,700	0	12,700	0	0.0%	0.0%	0	0.0%
Highland Avenue from I-95 NB Ramps to I-95 SB Ramps	12,381	14,500	2,119	17.1%	14,700	200	14,700	1.4%	14,700	200	14,900	200	17,700	3,000	20.4%	20.4%	3,000	20.4%
Highland Avenue from I-95 NB Ramps to Twp Line Rd (15th St)	12,016	14,300	2,284	19.0%	9,500	-4,800	9,500	-33.6%	9,500	4,200	13,700	4,200	16,200	6,700	70.5%	70.5%	6,700	70.5%
Highland Avenue from Twp Rd (15th St) to US 13 (9th St)	14,281	16,300	2,019	14.1%	15,500	-800	15,500	-4.9%	15,500	300	15,800	300	15,800	300	1.9%	1.9%	300	1.9%
Highland Avenue from US 13 (9th St) to PA 291 (2nd St)	7,652	9,200	1,548	20.2%	8,600	-600	8,600	-6.5%	8,600	100	8,700	100	8,800	200	2.3%	2.3%	200	2.3%
Township Line Road (15th St) from US 322 Ramp to Highland Ave.	9,751	12,000	2,249	23.1%	11,500	-500	11,500	-4.2%	11,500	-500	11,000	-500	5,600	-5,900	-51.3%	-51.3%	-5,900	-51.3%



I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Inset 12A. Current and 2034 No-Build Alternative Average Daily Traffic Volumes



Delaware Valley Regional
Planning Commission
March 2008

Traffic movements from US 322 eastbound to I-95 northbound and from I-95 southbound to US 322 westbound increase to 19,700 and 19,900 vpd, respectively. These volumes represent increases of 5,900 and 3,800 vpd over current traffic volumes. Other I-95 / US 322 interchange ramps increase by 1,200 to 2,100 vpd over existing values

Figure 13 shows the 2034 daily traffic forecasts for the three Build alternatives, along with the comparable No-Build Alternative forecasts. The additional capacity along I-95 provided by the various Build alternatives reduces conflicts and delays associated with merging and weaving traffic throughout the interchange area. This additional capacity does not, however, attract or divert a large number of new trips into the area.

Along I-95, average daily traffic volumes under the No-Build and all three Build alternatives differ by less than 1,000 vpd at all locations except between PA 452 and US 322. At this location, daily volumes vary by as much as 4,100 vpd. Under the No-Build Alternative, this volume is 129,300 vpd. It increases by 1,200 vpd to 130,500 vpd under Build Alternative 1. Build Alternative 2 has a slightly lower volume at 130,100, while the Build Alternative 3 volume is 133,400.

Traffic volumes along US 322 in 2034 under the various Build alternatives, in contrast, are significantly higher than the No-Build Alternative volume at study area locations west of I-95. For example, Build Alternative 1 volumes are 3,100 to 3,400 vpd, or 7.2 to 7.4 percent, higher than the comparable No-Build Alternative volumes. Build Alternative 2 volumes are only 100 to 200 vpd lower than the corresponding Build Alternative 1 volumes. Build Alternative 3 volumes, however, are 4,900 to 5,700 vpd higher than the No-Build Alternative volumes and are 1,800 to 2,600 vpd higher than the other Build Alternative volumes.

The proposed ramps between US 322 eastbound and I-95 southbound in all Build alternatives and between I-95 northbound and US 322 westbound in Build Alternative 3 are largely responsible for these differences in traffic volumes. The proposed ramp from US 322 eastbound to I-95 southbound carries 2,700 to 2,900 vpd in 2034 under the Build alternatives. The proposed ramp from I-95 northbound to US 322 westbound in Build Alternative 3 also carries 2,900 vpd in 2034.

These proposed ramps also affect traffic volumes at the I-95 / PA 452 interchange. The on-ramp from PA 452 to I-95 southbound volume is reduced by 500 to 1,200 vpd, compared to the No-Build Alternative volume. The off-ramp from I-95 northbound to PA 452 is reduced by 1,700 vpd under Build Alternative 3, compared to the No-Build Alternative.


PA 452 volumes are also lower under the Build alternatives than under the No-Build Alternative. In 2034, these reductions range from 900 to 2,000 vpd, which is about five to seven percent of the No-Build Alternative volume. The greatest reductions occur under Build Alternative 3 and the smallest occur under Build Alternative 1.

I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 13. 2034 No-Build and Build Alternatives 1, 2, and 3

Average Daily Traffic Volumes

- 46.7** 2034 Build Alternative 3 AADT (000s)
- 44.8** 2034 Build Alternative 2 AADT (000s)
- 44.9** 2034 Build Alternative 1 AADT (000s)
- 41.8** 2034 No-Build Alternative AADT (000s)




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Inset 13A. 2034 No-Build Alternative and Build Alternative 1 Average Daily Traffic Volumes




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Inset 13B. 2034 No-Build Alternative and Build Alternative 2 Average Daily Traffic Volumes



I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Inset 13C. 2034 No-Build Alternative and Build Alternative 3 Average Daily Traffic Volumes



Most other facilities in the study area have very similar traffic volumes under the No-Build and the three Build Alternatives. An exception is the area around Township Line Road, 15th Street, and Highland Avenue. The various locations of the I-95 northbound off- and on-ramps and the US 322 eastbound off-ramp to Township Line road cause the volumes in this area to vary significantly between alternatives.

D. 2034 AM and PM Peak Hour Traffic Forecasts

AM and PM peak hour traffic forecasts for 2034 under the No-Build Alternative are shown in Figure 14. Along I-95, peak hour volumes range from 4,830 to 6,790 vehicles per hour (vph). These volumes represent significant increases over current peak hour volumes. Along I-95 northbound, in the weaving area between Exit 3 and Exit 4, there will be an additional demand of over 1,000 vehicles during the AM peak hour and 850 vehicles during the PM peak hour.

Peak hour traffic forecasts on US 322 are between 1,310 and 1,810 vph west of I-95. These volumes represent increases of approximately 400 to 600 vph over current traffic levels. Higher volumes occur on US 322 east of I-95 on the approach to the Commodore Barry Bridge. Here, 2034 peak hour volumes under the No-Build Alternative range from 1,960 to 3,020 vph. The ramp from US 322 eastbound to I-95 northbound and the reverse movement from I-95 southbound to US 322 westbound also exhibit large increases over current volumes. They increase by approximately 300 to 400 vph during the AM and PM peak hours.


Volumes along PA 452 increase by approximately 200 to 300 vph in both the eastbound and westbound directions during both the AM and the PM peak hours. Traffic growth on streets that intersect with PA 452 is less pronounced. Except for Duttons Mill Road, there are few locations that increase by more than 50 vph. Peak hour volumes on Duttons Mill Road in 2034, however, will be approximately 200 vph over current volumes under the No-Build Alternative.

Peak hour traffic volumes in 2034 under Build Alternative 1 tend to be slightly higher than the corresponding No-Build volumes along both I-95 and US 322. The most significant differences occur on US 322 eastbound as it approaches the I-95 interchange at Exit 3 and on I-95 northbound between exits 3 and 4. Peak hour volumes on US 322 eastbound are approximately 250 vph higher than the corresponding No-Build Alternative volume, while I-95 northbound volumes are 120 to 130 vph higher under Build Alternative 1.

The new US 322 eastbound ramp to I-95 southbound will serve 210 and 250 vehicles in the AM and PM peak hours, respectively. The relocated I-95 northbound on-ramp from Highland Avenue to Township Line Road serves 30 to 40 additional vehicles in the peak hours, compared to the No-Build Alternative.


I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 14A. 2034 No-Build Alternative AM / PM Peak Hour Traffic Volumes



I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 14B. 2034 No-Build Alternative
AM / PM Peak Hour Traffic Volumes



Peak hour traffic volumes on most other study area facilities, including PA 452, are largely unchanged from the No-Build Alternative. One exception, however, is the I-95 southbound on-ramp from PA 452, where volumes are 40 vph lower than the No-Build Alternative volumes. Figure 15 provides the 2034 AM and PM peak hour traffic forecasts under Build Alternative 1.


Build Alternative 2 peak hour volumes are very similar to the Build Alternative 1 peak hour volumes. For example, the largest difference in I-95 volumes between the two alternatives is only 30 vph, and the largest difference in US 322 volumes is only 20 vph. The only significant differences are in the area of Highland Avenue, Township Line Road, and 15th Street, due to the relocation of the I-95 northbound on-ramp from Highland Avenue to 15th Street. There are also no significant differences in PA 452 volumes between Build alternatives 1 and 2. At all locations, the peak hour through movement volumes are within 30 vph of one another. Individual left- and right-turning volumes are within 10 vph of one another. Figure 16 displays the 2034 AM and PM peak hour traffic forecasts for Build Alternative 2.

Peak hour traffic volumes in 2034 under Build Alternative 3 are slightly higher than either of the other Build alternatives at most locations along I-95. The largest difference (190 vph) occurs between Build alternatives 2 and 3 in the northbound direction between the PA 452 and US 322 interchanges, during the PM peak hour. When compared to the No-Build Alternative, Build Alternative 3 volumes along I-95 are as much as 230 vph higher. US 322 volumes are also higher than the other Build alternative volumes. US 322 westbound volumes between I-95 and Bethel Road are 200 to 230 vph higher than Build Alternative 1 and Build Alternative 2 volumes during the peak hours. They are also 240 to 260 vph higher than the corresponding volumes under the No-Build Alternative.

Build Alternative 3 tends to have the lowest peak hour volumes along PA 452. Compared to Build Alternative 2, westbound PA 452 volumes are generally 50 to 90 vph lower during both the AM and PM peak hours. They are also 120 to 130 vph lower than the corresponding No-Build Alternative volumes. Figure 17 provides the 2034 AM and PM peak hour traffic forecasts under Build Alternative 3.


I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 15A. 2034 Build Alternative 1 AM / PM Peak Hour Traffic Volumes




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 15B. 2034 Build Alternative 1
AM / PM Peak Hour Traffic Volumes




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 16A. 2034 Build Alternative 2 AM / PM Peak Hour Traffic Volumes




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 16B. 2034 Build Alternative 2 AM / PM Peak Hour Traffic Volumes




I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 17A. 2034 Build Alternative 3 AM / PM Peak Hour Traffic Volumes



I-95 / US 322 INTERCHANGE TRAFFIC STUDY

Figure 17B. 2034 Build Alternative 3 AM / PM Peak Hour Traffic Volumes



[This page intentionally left blank]

VI. CONCLUSIONS

The I-95 / US 322 Interchange traffic study supports an interchange reconstruction project that is intended to increase safety and improve the flow of traffic through the interchange. This project will address a major weaving movement across three lanes of I-95 traffic. Currently, US 322 eastbound merges with the left-most lane of I-95 northbound at Exit 3, and continues towards the Commodore Barry Bridge via a right-side off-ramp at Exit 4. Because of the close proximity of Exits 3 and 4, this weaving movement often causes conflicts with through traffic that result in traffic backups and compromises safety. Other issues to be addressed include substandard acceleration and deceleration lanes and the lack of a connection from US 322 eastbound to I-95 southbound.

Traffic volumes along I-95 in this area range from 110,200 to 145,900 vehicles per day (vpd). US 322 volumes west of I-95 range from 27,600 to 33,400 vpd. East of I-95, as it approaches the Commodore Barry Bridge, US 322 carries a slightly higher volume of 35,400 vpd. The next highest volume facility in the study area is PA 452, which carries between 16,800 and 23,600 vpd.

By 2034, if no improvements are made to the interchange, volumes on I-95 in the study area will range from 126,300 to 172,400 vpd, representing increases of 14.6 to 18.2 percent over current levels. South of the I-95 / US 322 interchange, daily volumes are forecast to be 16,100 to 17,200 vpd higher than current volumes. Just north of the interchange, No-Build volumes will be 26,500 vpd higher than existing volumes. And further north of the Commodore Barry Bridge interchange at Exit 4, 2034 No-Build volumes will be 22,500 to 23,800 vpd higher than current volumes.

To address the existing deficiencies and to accommodate future growth in traffic volumes, three Build Alternatives have been proposed. These Build alternatives take different approaches to eliminate the US 322 eastbound weave, but all three provide for a right-side merge onto I-95 northbound. All three Build alternatives also include a new connection from US 322 eastbound to I-95 southbound and provide for some minor I-95 widening through the interchange area. In addition, Build Alternative 3 includes a new ramp from I-95 northbound to US 322 westbound.

The additional capacity along I-95 provided by the various Build alternatives will reduce conflicts and delays associated with merging and weaving traffic throughout the interchange area. This additional capacity does not, however, attract or divert a large number of new trips onto this section of I-95. Along I-95, average daily traffic volumes under the No-Build and all three Build alternatives differ by less than 1,000 vpd at all locations except between PA 452 and US 322. Volumes at this location are affected by the new ramp(s) between US 322 and I-95.

The proposed ramp from US 322 eastbound to I-95 southbound carries 2,700 to 2,900 vpd in 2034 under the Build alternatives. The proposed ramp from I-95 northbound to US 322 westbound in Build Alternative 3 also carries 2,900 vpd in 2034.

Traffic volumes along US 322 in 2034 under the various Build alternatives are higher than the No-Build Alternative volume at study area locations west of I-95. Build Alternative volumes are 3,100 to 5,700 vpd higher than the comparable No-Build Alternative volumes. However, PA 452 volumes are lower under the Build alternatives than under the No-Build Alternative. In 2034, these reductions range from 900 to 2,000 vpd. The greatest reductions occur under Build Alternative 3 and the smallest occur under Build Alternative 1.

These changes in daily traffic volumes translate into corresponding changes in peak hour volumes. That is, there will be large increases in AM and PM peak hour traffic volumes in 2034 compared to current conditions. There will not, however, be significant differences in peak hour traffic volumes between No-Build and Build conditions, or between the various Build alternatives.

I-95 / US 322 Interchange Traffic Study

Publication Number: 08024

Date Published: April 2008

Geographic Area Covered: The municipalities of Aston Township, Bethel Township, Brookhaven Borough, Chester City, Chester Township, Eddystone Borough, Lower Chichester Township, Marcus Hook Borough, Parkside Borough, Trainer Borough, Upland Borough, and Upper Chichester Township in Delaware County, Pennsylvania.

Key Words: I-95, US 322, Traffic Forecasts, Travel Simulation, AADT, Peak Hour Volumes, Intersection Turning Movements.

ABSTRACT

This report documents 2014 and 2034 traffic forecasts for the I-95 / US 322 Interchange and surrounding area in Delaware County. Average daily and AM and PM peak hour forecasts are provided for a No-Build and three Build alternatives and compared to current volumes.

Delaware Valley Regional Planning Commission
190 North Independence Mall West, 8th Floor
Philadelphia, PA 19106-1520

Phone: 215-592-1800
Fax: 215-592-9125
Internet: www.dvrpc.org

Staff Contact: Matthew T. Gates
Direct Phone: 215-238-2911
Email: mgates@dvrpc.org

